



AGRIMAX V-FLECTO - Загрузить лист технических данных



Description

Шины AGRIMAX V-FLECTO — это ответ компании BKT на потребность в технологиях и характеристиках для высокомоощных тракторов. Эти шины идеально подходят для обработки почвы и грузоперевозок за счет сниженного уплотнения почвы и способности к самоочищению. Благодаря инновационной технологии VF шины AGRIMAX V-FLECTO могут выдерживать большие нагрузки при низком давлении воздуха в них по сравнению со стандартными шинами и шинами с технологией IF. Кроме того, они хорошо зарекомендовали себя при движении на высокой скорости. Эти шины также характеризуются опцией узкого обода, что позволяет устанавливать их на стандартные ободья. Компания BKT разработала эти шины с оптимизированной геометрией для повышения комфорта движения как в поле, так и на дороге с одновременным уменьшением расхода топлива.

UM

International Standard

Construction



RADIAL

Machinery

Сельское хозяйство: Трактор высокой мощности

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	NRO	SW	OD	SLR	RC	SRI	Type	ECE
VF 280/70 R 18	STANDARD		116 D	W 9	9		274	849	375	2515	400	TL	E11-106R-0010341
VF 340/85 R 28	STANDARD		139 D	W 12	W 11		355	1290	571	3833	625	TL	E11-106R-0010342
VF 480/60 R 28 NRO	STANDARD	R1W	145 D	DW 16 L	W 16 L	W 15 L	470	1290	571	3807	625	TL	E11-106R-005496
VF 520/60 R 28 NRO	STANDARD	R1W	149 D	DW 18 L	W 18 L	DW 16 L	516	1335	587	3910	650	TL	E11-106R-005497
VF 540/65 R 28 NRO	STANDARD	R1W	154 D	DW 20 B	DW 18 L	DW 16 L	549	1413	622	4160	675	TL	E11-106R-005710
VF 600/60 R 28 NRO	STANDARD	R1W	157 D	DW 20 B	DW 18 L	DW 18 L	587	1440	632	4228	675	TL	E11-106R-004471
VF 600/65 R 28 NRO	STANDARD	R1W	163 D	DW 21 B	DW 20 B	DW 18 L	597	1491	655	4453	700	TL	E11-106R-007602
VF 600/70 R 28 NRO	STANDARD	R1W	167 D	DW 21 B	DW 20 B	DW 18 L	603	1551	662	4596	725	TL	E11-106R-008814
VF 480/70R30	STANDARD		153 D	W 18 L	W 16 L ; DW 18 L	W 15 L	495	1430	645	4353	675	TL	E11-106R-0010762
VF 540/65 R 30 NRO	STANDARD	R1W	158 D	DW 20 B	DW 18 L	DW 16 L	549	1464	650	4351	700	TL	E11-106R-005711
VF 600/60 R 30 NRO	STANDARD	R1W	158 D	DW 20 B	DW 18 L ; DW 21 B	DW 18 L	595	1485	649	4404	700	TL	E11-106R-002979
VF 600/70 R 30 NRO	STANDARD		168 D	DW 21 B	DW 20 B	DW 18 B	603	1602	702	4711	750	TL	E11-106R-006162
VF 710/60 R 30	STANDARD	R1W	171 D	DW 25 B	DW 24 B ; DW 27 B	DW 23 B	720	1625	701	4801	775	TL	E11-106R-0010832
VF 480/70 R 34 NRO	STANDARD		166 D	W 18 L	W 16 L ; DW 18 L	W 15 L	495	1580	708	4739	750	TL	E11-106R-0010578
VF 600/60 R 34	STANDARD	R1W	160 D	DW 20 B	DW 18 L ; DW 21 B	DW 18 L	595	1584	691	4710	750	TL	E11-106R-008773
VF 600/65 R 34 NRO	STANDARD	R1W	169 D	DW 21 B	DW 20 B	DW 18 L	597	1644	731	4952	775	TL	E11-106R-007603
VF 600/70 R 34 NRO	STANDARD	R1W	170 D	DW 21 B	DW 20 B	DW 18 B	603	1704	740	5025	800	TL	E11-106R-008813
VF 650/60 R 34	STANDARD		168 D	DW 23 B	DW21B		660	1676	750	4996	775	TL	E11-106R-007210
VF 650/65 R 34 NRO	STANDARD	R1W	170 D	DW 23 B	DW 21 B	DW 20 B	650	1710	756	5110	825	TL	E11-106R-008812
VF 710/55 R 34	STANDARD	R1W	170 D	DW 25 B	DW 27 B	DW 23 B	708	1659	726	4910	775	TL	E11-106R-0010831
VF 710/60 R 34 NRO	STANDARD	R1W	173 D	DW 25 B	DW 24 B ; DW 27 B	DW 23 B	708	1716	752	5097	825	TL	E11-106R-007201

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	NRO	SW	OD	SLR	RC	SRI	Type	ECE
VF 480/80 R 38	STANDARD	R1W	166 D	DW 16 L	DW 15 L		479	1733	774	5169	825	TL	E11-106R-007168
VF 520/70 R 38	STANDARD	R1W	164 D	DW 18 L			536	1750	773	5213	825	TL	E11-106R-0011692
VF 540/65 R 38 NRO	STANDARD	R1W	162 D	DW 20 B	DW 18 L	DW 16 L	549	1676	760	4981	800	TL	E11-106R-005020
VF 600/60 R 38 NRO	STANDARD	R1W	168 D	DW 20 B	DW 18 L	DW 18 L	587	1685	757	5077	800	TL	E11-106R-006414
VF 600/60 R 38 NRO	STANDARD	R1W	166 D	DW 20 B	DW 18 L	DW 18 L	587	1685	757	5081	800	TL	E11-106R-005021
VF 650/60 R 38 NRO	STANDARD	R1W	173 D	DW 23 B	DW 21 B	DW 20 B	650	1745	774	5217	825	TL	E11-106R-006415
VF 650/60 R 38 NRO	STANDARD	R1W	166 D	DW 23 B	DW 21 B	DW 20 B	650	1745	774	5231	825	TL	E11-106R-005712
VF 650/65 R 38 NRO	STANDARD	R1W	169 D	DW 23 B	DW 21 B	DW 20 B	650	1811	798	5387	875	TL	E11-106R-005022
VF 650/75 R 38 NRO	STANDARD	R1W	175 D	DW 23 B	DW 21 B	DW 20 B	675	1941	833	5796	925	TL	E11-106R-0010663
VF 650/85 R 38	STANDARD	R1W	182 D	DW 23 B	DW 20 B ; DW 21 B	DW 20 B	670	2071	887	6119	975	TL	E11-106R-0010945
VF 650/85 R 38 CFO	SPECIAL	R1W	182 D	DW 23 B	DW 20 B ; DW 21 B		670	2071	887	6119	975	TL	E11-106R-0010579
VF 710/55 R 38	STANDARD	R1W	175 D	DW 25 B	DW 24 B		710	1750	780	5242	825	TL	E11-106R-006844
VF 710/60 R 38 NRO	STANDARD	R1W	171 D	DW 25 B	DW 23 B	DW 23 B	708	1820	794	5447	875	TL	E11-106R-004520
VF 710/70 R 38	STANDARD		181 D	DW 24 B	DW 23 B ; DW 25 B		715	1961	843	5773	925	TL	E11-106R-006163
VF 710/75 R 38	STANDARD	R1W	183 D	DW 24 B	DW 23 B ; DW 25 B		720	2060	905	6151	950	TL	E11-106R-006764
VF 800/70 R 38 CFO	STANDARD		187 D	DW 28 B	DW25 B ; DW27B ; DW30B		804	2085	890	6155	975	TL	E11-106R-007205
VF 900/60 R 38 NRO	STANDARD	R1W	187 D	DW 30 B		DW 27 B	881	2045	882	6053	975	TL	E11-106R-009004
VF 580/85 R 42 CFO	SPECIAL	R1W	183 D	DW20B	DW18B ; MW20B		606	2058	923	6166	975	TL	E11-106R-006444
VF 580/85 R 42 CFO	STANDARD	R1W	183 D	DW20B	DW18B ; MW20B		606	2058	923	6166	975	TL	E11-106R-006444
VF 620/70 R 42	STANDARD		175D	DW 21 B	DW 20 B ; DW 23 B		620	1935	849	5795	925	TL	E11-106R-0011233
VF 620/70 R 42 CFO	SPECIAL		175D	DW 21 B	DW 20 B ; DW 23 B		620	1935	849	5795	925	TL	E11-106R-0010829
VF 650/60 R 42	STANDARD		174 D	DW 23 B	DW21B		660	1845	834	5564	875	TL	E11-106R-008774

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	NRO	SW	OD	SLR	RC	SRI	Type	ECE
VF 650/65 R 42 NRO	STANDARD	R1W	174 D	DW 23 B	DW 21 B	DW 20 B	650	1913	852	5773	925	TL	E11-106R-005713
VF 650/75 R 42 CFO	SPECIAL	R1W	180 D	DW 23 B	DW 21 B	DW 20 B	680	2055	895	6143	975	TL	E11-106R-0011304
VF 650/85 R 42 CFO	SPECIAL	R1W	183 D	DW 23 B	DW20B;DW21B		680	2160	938	6413	1025	TL	E11-106R-0011307
VF 710/60 R 42 NRO	STANDARD	R1W	173 D	DW 25 B	DW 23 B ; MW 25 B	DW 23 B	710	1930	860	5786	925	TL	E11-106R-002998
VF 710/70 R 42	STANDARD		185 D	DW 25 B	DW 23 B; DW 24 B		715	2061	921	6182	975	TL	E11-106R-0010959
VF 710/70 R 42	STEEL BELTED		193 D	DW 25 B	DW 23 B; DW 24 B		720	2058	928	6233	975	TL	E11-106R-0010960
VF 710/70 R 42 CFO	SPECIAL		185 D	DW 25 B	DW 23 B; DW 24 B		715	2061	909	6182	975	TL	E11-106R-006266
VF 710/70 R 42 CFO	STEEL BELTED SPL		193 D	DW 25 B	DW 23 B; DW 24 B		720	2058	928	6233	975	TL	E11-106R-009053
VF 710/75 R 42	STANDARD	R1W	184 D	DW 24 B	DW 23 B ; DW 25 B		730	2150	937	6412	1000	TL	E11-106R-009074
VF 900/60 R 42 CFO	SPECIAL		189 D	DW 30B		DW 28 B	900	2142	937	6390	1025	TL	E11-106R-006165
VF 900/60 R 42 CFO	STEEL BELTED		195 D	DW 30B		DW 28 B	900	2142	944	6410	1025	TL	E11-106R-0010587
VF 900/60 R 42 NRO	STANDARD		189 D	DW 30B		DW 28 B	900	2142	937	6390	1025	TL	E11-106R-006165
VF 750/70 R 44	STANDARD	R1W	186 D	DW 25 B	DW 24 B		760	2175	958	6450	1025	TL	E11-106R-006765
VF 480/80 R 46 CFO	STEEL BELTED		175 D	DW 16 L	DW 15 L		479	1940	892	5855	925	TL	E11-106R-0010596
VF 520/85 R 46	STANDARD	R1W	173 D	DW 18 L			535	2052	911	6111	975	TL	E11-106R-008662
VF 520/85 R 46 CFO	SPECIAL	R1W	173 D	DW 18 L			535	2052	911	6111	975	TL	E11-106R-008662
VF 580/85 R 46	STANDARD	R1W	179 D				605	2156	947	6451	1025	TL	E11-106R-0011691
VF 710/60 R 46	STANDARD	R1W	174 D	DW 25 B	DW 27 B		715	2041	896	6092	975	TL	E11-106R-0010941
VF 710/60 R 46 CFO	SPECIAL	R1W	174 D	DW 25 B	DW 27 B	DW 20 B	715	2041	896	6092	975	TL	E11-106R-0011234
VF 900/65 R 46	STANDARD		193 D	DW 30B		DW 28 B	920	2315	1003	6886	1100	TL	E11-106R-0011165
VF 900/65 R 46	STEEL BELTED		193 D	DW 30B		DW 28 B	900	2338	1006	7003	1100	TL	E11-106R-0010961
VF 900/65 R 46 CFO	SPECIAL		193 D	DW 30B		DW 28 B	920	2315	1003	6886	1100	TL	E11-106R-0011166

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	NRO	SW	OD	SLR	RC	SRI	Type	ECE
VF 900/85 R 46 CFO	STEEL BELTED SPL		193 D	DW 30B		DW 28 B	900	2338	1006	7003	1100	TL	E11-106R-0010524
VF 480/80 R 50 CFO	STEEL BELTED		179 D	DW16L	DW15L		479	2038	938	6195	975	TL	E11-106R-0010595
VF 520/85 R 50	STEEL BELTED	R1W	177 D	DW 18 L	DW 16 L		535	2160	972	6493	1025	TL	E11-106R-0011305
VF 520/85 R 50 CFO	STEEL BELTED SPL	R1W	177 D	DW 18 L	DW 16 L		535	2160	972	6493	1025	TL	E11-106R-0011305

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09.12.2025 9:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..